

Bảng thông số sản phẩm

Thông số kỹ thuật



APC Performance SurgeArrest 6 outlets 3 Meter Cord 230V Vietnam

PM63-VN



Overview

Lead time Usually in Stock

Main

Main Input Voltage 220 V
230 V
240 V

Input Connection Type NEMA 5-15P

Cable length 3.00 m

Number of cables 1

Provided equipment User manual

Physical

Colour White

Height 27.15 cm

Width 11.03 cm

Depth 6.17 cm

Net weight 0.7 kg

Mounting preference No preference

Mounting mode Rack-mounted

Input

Input power 2300 W

Network frequency 50/60 Hz

Maximum input current 10 A

Switching current capacity 10 A

Output

Number of power socket outlets 6

Outlet standard NEMA universal

Miễn trừ trách nhiệm: Tài liệu này không nhằm thay thế và không được sử dụng để xác định tính phù hợp hoặc độ tin cậy của các sản phẩm này cho các ứng dụng người dùng cụ thể.

Conformance

Equipment protection policy No EPP for ASEAN

Environmental

Ambient air temperature for operation 0...40 °C

Relative humidity 0...95 % non-condensing

Operating altitude 0...10000 ft

Ambient air temperature for storage -15...45 °C

Storage Relative Humidity 0...95 %

Storage altitude 0.00...15240.00 m

Surge Protection and Filtering

Response time 1 ns common mode

Common mode rejection 40 dB

Peak current 48 kA common mode
24 kA normal mode

Surge energy rate 1836 J

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Package 1 Height 31 cm

Package 1 Width 6.5 cm

Package 1 Length 16.5 cm

Package 1 Weight 0.82 kg

SCC14 10731304343131

Offer Sustainability

Sustainable offer status Green Premium product

REACH Regulation [REACH Declaration](#)

REACH free of SVHC Yes

EU RoHS Directive Compliant
[EU RoHS Declaration](#)

Mercury free Yes

RoHS exemption information [Yes](#)

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)

Contractual warranty

Warranty 10 years repair or replace

Thay thế được đề xuất