

Bảng thông số sản phẩm

Thông số kỹ thuật



Switch, AvatarOn A, 20A 250V, Double Pole, with LED S sized, White

M3T31_D20N_WE

Main

Range Of Product	AvatarOn A
Product Or Component Type	Switch
Load Type	Resistive load Inductive
Colour Tint	White (WE)
Colour Tint	White

Complementary

Device Presentation	Complete product
Rated Current	20 A at 250 V AC 50 Hz
Switch Function	2-pole
Switch Application	Control switch
Clamping Connection Capacity	2 x 1.5 mm ² for solid cable(s) 2 x 2.5 mm ² for stranded cable(s) 2 x 4 mm ²
Connections - Terminals	Screwless type terminals
Local Signalling	Fluorescent (white)
Material	PC: dolly PC 10 % GF: base PC 10 % GF: base cover
Device Mounting	Flush
Width	23.1 mm
Height	69.3 mm
Depth	35 mm
Embedding Depth	24 mm

Environment

Ip Degree Of Protection	IP20
Maximum Ambient Air Temperature For Operation	45 °C
Ambient Air Temperature For Storage	-5...60 °C
Operating Altitude	<= 2000 m
Relative Humidity	0...95 %
Standards	IEC 60669-1

Product Certifications	IEC TIS
------------------------	------------

Packing Units

Unit Type Of Package 1	PCE
------------------------	-----

Number Of Units In Package 1	1
------------------------------	---

Package 1 Height	3.6 cm
------------------	--------

Package 1 Width	2.3 cm
-----------------	--------

Package 1 Length	7.0 cm
------------------	--------

Package 1 Weight	34.0 g
------------------	--------

Unit Type Of Package 2	BB1
------------------------	-----

Number Of Units In Package 2	20
------------------------------	----

Package 2 Height	9.1 cm
------------------	--------

Package 2 Width	8.9 cm
-----------------	--------

Package 2 Length	25.5 cm
------------------	---------

Package 2 Weight	731.0 g
------------------	---------

Unit Type Of Package 3	S03
------------------------	-----

Number Of Units In Package 3	240
------------------------------	-----

Package 3 Height	30.0 cm
------------------	---------

Package 3 Width	30.0 cm
-----------------	---------

Package 3 Length	40.0 cm
------------------	---------

Package 3 Weight	9.422 kg
------------------	----------

Bền vững

Nhãn **Green Premium™** là cam kết của Schneider Electric trong việc cung cấp sản phẩm với hiệu suất môi trường tốt nhất. Green Premium cam kết tuân thủ các quy định mới nhất, minh bạch về tác động môi trường, cũng như các sản phẩm tuần hoàn và CO₂ thấp.

Hướng dẫn đánh giá tính bền vững của sản phẩm là tài liệu kỹ thuật phổ thông giúp làm rõ các tiêu chuẩn nhãn sinh thái toàn cầu và cách diễn giải việc khai báo môi trường.

[Tìm hiểu thêm về Green Premium >](#)

[Hướng dẫn đánh giá về sự bền vững của sản phẩm >](#)



Minh bạch **RoHS/REACH**

Hiệu suất sức khỏe



Mercury Free



Rohs Exemption Information

Yes

Chứng nhận & Tiêu chuẩn

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant with Exemptions

China Rohs Regulation

[China RoHS declaration](#)

Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure

[Product Environmental Profile](#)

Circularity Profile

No need of specific recycling operations