

Light is OSRAM

OSRAM

## ELEMENT 30/220-240/12 G2

### 12V Constant Voltage LED driver

A smart choice for the decorative lighting, well tested by OSRAM quality standard, fits 12V Flex & Signage applications in retails, hotels, restaurants, etc.

#### Benefits

Well design for Flex and Signage  
High efficiency up to 86%  
High Power Factor  
Class II design for wide application  
Excellent price/quality/watt ratio  
Suitable for Class I/II luminaires



#### Applications

Hospitality – decorative lighting, night light  
Restaurants – decorative lighting  
Shops – decorative lighting, shelf lighting  
Residential – cove lighting, under cabinet lighting

#### Approval marks



In preparation, if not already printed on product label



145 x 40 x 26.5 mm  
Housing material: Plastic


### Product Features

- 12 V constant output voltage
- Output power up to 30W
- Wide  $t_a$  range -20 ... +50 °C
- Mains voltage: 220 – 240 V<sub>AC</sub>
- High efficiency up to 86%
- PF>0.95
- Screw terminals
- Integrated cable clamp
- Overload protection
- Over temperature protection
- Short circuit protection
- $t_c$  max = 80 °C
- 30'000 h lifetime at  $t_c$  of 80°C
- 3 years guarantee
- Suitable for Class I / II luminaires
- Matching with OSRAM dimmers

## Electrical specifications

	Item	Value	Unit	Remarks
Input	Nominal voltage	220 – 240	V	
	Nominal frequency	50 / 60	Hz	
	AC voltage range	198 – 264	V	
	DC voltage range	n/a		
	Maximum voltage	280	Vac	2 h maximum, unit might not operate in this abnormal Condition
	Nominal current	0.2	A	At 230 Vac
	Total Harmonic Distortion (THD)	<15	%	Full load, 230 Vac, 50 Hz / 60 Hz see graphs
	Power factor	0.95		Typical, Full load, 230 Vac, 50 Hz / 60 Hz, see graphs
	Efficiency	86	%	Typical, Full load, 230Vac, 50Hz, see graphs
	Power losses	4.9	W	Full load, 230 Vac, 50Hz / 60Hz
	No-load power	n/a		
	Protection class	II		Suitable for safety class I and II luminaires
	Touch current	<0.7	mA pk	Through Equi PIN, LED Output floating, acc. to EN 60598-1 Annex G and EN 61347-1 Annex A
	Inrush current	13.2	A pk	Max, t = 200 µs
	Max. units per circuit breaker	B10: 29, B16: 47, B25: 74, C10: 46, C16: 73, C25: 114		
Output	Nominal output voltage	12.5	V	
	Voltage accuracy	+2.5/- 3	%	
	Voltage ripple	< 3	%	Ripple / average @ 100 Hz; Full load
	Nominal output power	30	W	
	Maximum power	30	W	LED output
	Capacitive load	20	uF/A	
	Galvanic isolation	SELV		
	Dimmable	No		
	U-OUT	25	V	
ENVIRONMENTAL	Ambient temperature range	-20 - +50	°C	
	Max. temperature at tc test point operation	80	°C	Measured on tc point indicated of the prod label, ta not exceeded
	Max. case temp. in fault condition	110	°C	
	Storage temperature range	-40 - +85	°C	
	Permitted rel. humidity during	5 – 85	%	Not condensing
	Surge capability (L/N)	1	kV	L/N acc to. EN 61547
	Environmental rating	Indoor		
	IP protection class	IP 20		
	Mains switching cycles	> 50'000		
	Expected lifetime	30'000 50'000	h	At tc max with 10% failure rate At tc-10°C with 10% failure rate
	No-load proof	Yes		
	Overheating protection	Yes		Automatically restart
	Overload protection	Yes		Automatically restart
	Short-circuit protection	Yes		Automatically restart
	Dimension	145x40x26.5	mm	L x W x H
	Weight	100	g	
	Casing material	Plastic		

## Wiring diagram




## Cable and wire preparation

- Input wires cross section: 0.75 - 1,5 mm<sup>2</sup>
- Output wires cross section: 0.75-1.5 mm<sup>2</sup>
- Wire peeling length: input 5 mm; output 5 mm
- Load wires length: 3 m verified
- Screws are locked with 0.7nm torque
- Cable recommendation: H05VVH2-F 2\*0.75mm<sup>2</sup>; H05VVH2-F 2\*1.0mm<sup>2</sup>; H03VVH2-F 2x0.75mm<sup>2</sup>, H03VVH2-F 2x1.5mm<sup>2</sup>

## Led wire length


EMI pass verified with wire length below 3 m, within 70%-100% loading test condition. It is recommended to check the compliance of total system in design-in phase.

Electrical characteristics



## Remarks

- The driver withstands an input voltage of up to 280 Vac for maximum 2 hours. Shut down of output load might occur in case the supply voltage exceeds the declared input voltage range.
- The driver automatically reduces the output current in case the maximum allowed output power is exceeded.
- The driver switches off the output in case the load voltage still above the maximum allowed voltage.
- The driver is protected against temporary overheating by automatically reduces the output current, the protection is reversible.
- **Recommendations on how to dispose of it at the end of its life in line with Directive 2012/19/EU:** Separate control gear must be disposed of, in accordance with WEEE, at certified waste disposal companies. For this purpose, recycling centers and take-back systems (CRSO) collection points are available in the trade or at private disposal companies that accept separate control gears free of charge. In this way, raw materials are conserved, and materials are recycled.
- **Ecodesign regulation information:** Intended for use with LED modules. The forward voltage of the LED light source shall be within the defined operating window of the control gear in all operating conditions including dimming if applicable. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centers and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved, and materials are recycled.
- No-load conditions: hot plug-in or secondary switching of LEDs is not permitted. Please take care to switch the driver off via L.
- The independent type (with Cable clamp) of Element 12V G2 classified as "NON-IC": The control gear cannot be abutted against or covered by normally flammable materials or used in installations where building insulation or debris is, or may be, present in normal use. No use for residential installations. The minimum clearance distance from the top and sides of the independent LED driver to normally flammable building elements is A=B=C=10mm



## Ordering information

Product name	EAN 10	EAN 40	Pieces / box
ELEMENT 30/220-240/12 G2	4062172277846	4062172277853	40

## Standards

Safety:  
 EN/IEC 61347-1,  
 EN/IEC 61347-2-13  
 Performance:  
 EN/IEC 62384  
 Harmonic content:  
 EN/IEC 61000-3-2  
 Radio interference: CISPR 15  
 Immunity:  
 EN/IEC 61000-3-3  
 EN/IEC 61547

### OSRAM GmbH

Head Office:  
 Marcel-Breuer-Strasse 6  
 80807 Munich, Germany  
 Phone +49 89 6213-0  
 www.osram.com

# OSRAM