



# Light is infinity

## Product Portfolio Summary

Light is OSRAM

traxon e:cue

**OSRAM**

## General Lighting

### Downlight

| Product                                                                                                             | Description                                                                                                                                                   | Features & Benefits                                                                                                                                                                                                                               |                                                                                                |
|---------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|
|  <b>LEDTOUCH™<br/>Downlight</b>    | <ul style="list-style-type: none"> <li>4", 11W / 15W, 85 lm/W</li> <li>6", 20W / 28W / 40W, 100 lm/W</li> <li>8", 60W, 85 lm/W</li> </ul>                     | <ul style="list-style-type: none"> <li>Total solution and flexibility</li> <li>Outstanding light performance</li> <li>Robust design and safety</li> </ul>                                                                                         | <br>M050L08 |
|  <b>Simplitz®<br/>Downlight V2</b> | <ul style="list-style-type: none"> <li>4", 8W, 100 lm/W</li> <li>5", 11W, 110 lm/W</li> <li>6", 14.5W, 115 lm/W</li> <li>8", 20W / 27.5W, 120 lm/W</li> </ul> | <ul style="list-style-type: none"> <li>Integrated design with built-in driver</li> <li>Up to 120 lm/W</li> <li>50,000 hrs lifetime</li> <li>120 mm pre-wire</li> </ul>                                                                            | <br>M100L07 |
|  <b>LEDCOMFO®<br/>Downlight V3</b> | <ul style="list-style-type: none"> <li>4", 8W, 75 lm/W</li> <li>5", 10W, 80 lm/W</li> <li>6", 16W, 85 lm/W</li> <li>8", 24W, 90 lm/W</li> </ul>               | <ul style="list-style-type: none"> <li>Rigidity &amp; safety</li> <li>Uniform and comfortable lighting experience</li> <li>Wide mounting ring (10 mm to 12.5 mm) and slim design with the height of 35 mm</li> <li>30,000 hrs lifetime</li> </ul> | <br>M500L06 |

### Spot Light

| Product                                                                                                                | Description                                                                                                                                                                                                                                              | Features & Benefits                                                                                                                                                                                    |                                                                                                  |
|------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|
|  <b>LEDCOMFO®<br/>Spot Light HP</b>  | <ul style="list-style-type: none"> <li>3", 6W, 79-90 lm/W</li> <li>3.5", 9W, 70-80 lm/W</li> <li>4.5", 18W, 73-83 lm/W</li> <li>5.5", 30W, 77-88 lm/W</li> </ul>                                                                                         | <ul style="list-style-type: none"> <li>Flexible product options</li> <li>Quality light</li> <li>Reliable</li> </ul>                                                                                    | <br>M500L06  |
|  <b>LEDCOMFO®<br/>Spot Light V3</b> | <ul style="list-style-type: none"> <li>3.5", 3W, 65-73 lm/W</li> <li>3.5", 6W, 67-75 lm/W</li> <li>4", 8W, 70-75 lm/W</li> </ul>                                                                                                                         | <ul style="list-style-type: none"> <li>External driver offers high quality and reliability</li> <li>Accurate angle control on reflector to offer 30° beam angle</li> <li>Body ±20° tiltable</li> </ul> | <br>M500L06 |
|  <b>LEDCOMFO®<br/>Multi-head</b>    | <ul style="list-style-type: none"> <li>1 x 9W, 70-80 lm/W</li> <li>2 x 9W, 140-160 lm/W</li> <li>3 x 9W, 198-225 lm/W</li> <li>1 x 18W, 79-90 lm/W</li> <li>2 x 18W, 148-168 lm/W</li> <li>1 x 30W, 77-87 lm/W</li> <li>2 x 30W, 150-170 lm/W</li> </ul> | <ul style="list-style-type: none"> <li>Flexible product options</li> <li>Reliability and easy installation</li> <li>Quality light and energy saving</li> <li>25,000 hrs lifetime</li> </ul>            | <br>M500L06 |

### Track Light

| Product                                                                                                                           | Description                                                                                                                  | Features & Benefits                                                                                                                                                                                                                                                                    |                                                                                                  |
|-----------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|
|  <b>ADMIRE</b><br>(From Art Centric Lighting)  | <ul style="list-style-type: none"> <li>Tunable White, 20W, up to 60 lm/W</li> <li>Fixed White, 30W, up to 75 lm/W</li> </ul> | <ul style="list-style-type: none"> <li>Black or white finishing</li> <li>Beam angle variable from 12° to 50°</li> <li>Tunable white version from 2800K to 5600K</li> <li>Fixed color version (2700K / 3000K / 4000K)</li> <li>Control options: Manual, Dali, Bluetooth, DMX</li> </ul> | <br>M001L06 |
|  <b>APPLAUD</b><br>(From Art Centric Lighting) | <ul style="list-style-type: none"> <li>Tunable White, 20W, up to 60 lm/W</li> <li>Fixed White, 30W, up to 75 lm/W</li> </ul> | <ul style="list-style-type: none"> <li>With Gobo holder</li> <li>Black or white finishing</li> <li>Tunable white version from 2800K to 5600K</li> <li>Fixed color version (2700K / 3000K / 4000K)</li> <li>Control options: Manual, Dali, Bluetooth, DMX</li> </ul>                    | <br>M001L06 |
|  <b>CHARMY</b><br>(From Art Centric Lighting)  | <ul style="list-style-type: none"> <li>Tunable White, 33W, up to 72 lm/W</li> </ul>                                          | <ul style="list-style-type: none"> <li>Potentiometers on the back of the light to adjust light intensity and color</li> <li>Beam angle variable from 18° to 40°</li> <li>Tunable white from 1800K to 5200K</li> <li>Control options: Manual, Dali, Bluetooth, DMX</li> </ul>           | <br>M001L06 |
|  <b>RESPECT</b><br>(From Art Centric Lighting) | <ul style="list-style-type: none"> <li>Tunable White, 20W, up to 60 lm/W</li> <li>Fixed White, 30W, up to 75 lm/W</li> </ul> | <ul style="list-style-type: none"> <li>Black or white finishing</li> <li>Beam angle: 12°, 18°, 40°, 60°</li> <li>Tunable white version from 2800K to 5600K</li> <li>Fixed color version (2700K / 3000K / 4000K)</li> <li>Control options: Manual, Dali, Bluetooth, DMX</li> </ul>      | <br>M001L06 |


**LED COMFO®  
Track Light**

- S, 15W, 75-86 lm/W
- M, 25W, 60-68 lm/W
- L, 40W, 75-85 lm/W

- Flexible product options
- Convenience
- Quality light
- Rigidness



M500L06

## Panel


**Product**
**Simplitz® Panel**
**Description**

- Suspended
- 595 x 595 mm, 32W / 56W, 110 lm/W
- 1195 x 295 mm, 32W / 56W, 110 lm/W
- Integrated
- 600 x 600 mm, 32W / 56W, 110 lm/W
- 1200 x 300 mm, 32W / 56W, 110 lm/W

**Features & Benefits**

- Uniform light with no dark spot or yellow rim
- Integrated ceiling version that saves accessory cost
- Flicker free
- 50,000 hrs lifetime
- Dali & ON/OFF Version



M100L08


**LED COMFO®  
Panel G2**

- Suspended
- 595 x 595 mm, 35W, 100 lm/W
- 1195 x 295 mm, 35W, 100 lm/W
- 1195 x 595 mm, 56W, 100 lm/W
- Integrated
- 600 x 600 mm, 35W, 100 lm/W
- 1200 x 300 mm, 35W, 100 lm/W

- Excellent lighting effect
- High efficiency and reliability



M200L08

## Batten & Ribbon


**Product**
**Simplitz®  
Batten V3**
**Description**

- 585 mm, 16W, 130 lm/W
- 1170 mm, 16W / 33W, 130 lm/W

**Features & Benefits**

- Compact and lightweight design
- High efficiency up to 130 lm/W
- Robust Aluminum housing
- 50,000 hrs lifetime
- Surfaced mounted and suspended



M200L08


**Simplitz®**
**Cleanroom Batten**

- 4ft, 18W / 36W, 130 lm/W
- White (4000K, 5700K) or Amber

- Dedicated designed for cleanroom
- Amber version for photolithography area
- High efficiency, up to 130 lm/W
- 50,000 hrs lifetime
- No LED hot spot



M200L08


**LED COMFO®  
Batten G4**

- 1 ft, 4W, 80-84 lm/W
- 2 ft, 7W, 80-84 lm/W
- 3 ft, 10W, 79-84 lm/W
- 4 ft, 14W, 80-84 lm/W

- Double injection technology
- Robust structure with longer length
- 20,000 hrs lifetime
- Flicker-free



M500L08


**LED COMFO®  
Ribbon Fixture**

- 5m, 16.5W, 102-109(IP20) / 94-102(IP65) lm/W
- 5m, 29.5W, 99-106(IP20) / 91-99(IP65) lm/W
- 5m, 38.5W, 97-105(IP20) / 90-97(IP65) lm/W

- Optimized electric design to ensure brightness consistency from end to end
- 700 times 720° twisting test in design
- 20,000 hrs lifetime



M400L08

## High Low Bay


**Product**
**Simplitz®  
Highbay G2**
**Description**

- 260 mmØ, 50W / 75W, 140 lm/W
- 310 mmØ, 125W, 140 lm/W
- 400 mmØ, 175W / 225W, 140 lm/W

**Features & Benefits**

- Flexible options in optics, powers, controls, accessories and mounting methods
- Up to 140 lm/W
- Backup hook reserved for safety chain/cable
- IP65, IK08 and 50,000 hrs lifetime
- Versatile application



M100L07


**LED COMFO®  
Highbay V2**

- 245 mmØ, 70W, 110 lm/W
- 300 mmØ, 130W, 110 lm/W
- 350 mmØ, 200W, 110 lm/W

- One to one replacement for HID highbay with 50% energy saving
- Die-casting housing, IP65, IK08
- Visual comfort
- Compact and light weight




M200L08

## Waterproof

| Product                                                                                                          | Description                                                                                                                                 | Features & Benefits                                                                                                                                                                                                                                    |                                                                                                |
|------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|
|  <b>Simplitz® Waterproof</b>    | <ul style="list-style-type: none"> <li>1200 mm: 17W / 33W</li> <li>1500 mm: 28W / 50W</li> </ul>                                            | <ul style="list-style-type: none"> <li>Different combination of power options</li> <li>IP65, IK08 and 50,000 hrs lifetime</li> <li>Up to 120 lm/W</li> <li>Surface and suspended mounting</li> <li>Slim profile, suitable for limited space</li> </ul> | <br>M200L08 |
|  <b>ECOFITZ® LED Waterproof</b> | <ul style="list-style-type: none"> <li>2 ft, 20W, 100-150 lm/W</li> <li>4 ft, 40W, 105-110 lm/W</li> <li>5 ft, 48W, 105-110 lm/W</li> </ul> | <ul style="list-style-type: none"> <li>Unique prismatic lens</li> <li>Reliable</li> <li>Highly energy efficient and low maintenance</li> <li>Flexible mounting options</li> </ul>                                                                      | <br>M200L08 |

## Street Light

| Product                                                                                                                 | Description                                                                                                                                                                                       | Features & Benefits                                                                                                                                                                                                                         |                                                                                                  |
|-------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|
|  <b>Simplitz® LED Street Light</b>     | <ul style="list-style-type: none"> <li>Micro, 30W / 60W, 140 lm/W</li> <li>Mini, 90W, 140 lm/W</li> <li>Midi, 120W / 150W, 140 lm/W</li> <li>Maxi, 180W / 210W / 240W / 270W, 140 lm/W</li> </ul> | <ul style="list-style-type: none"> <li>Smart City compatibility</li> <li>Modern and simple design</li> <li>Comprehensive product range</li> <li>High efficacy up to 140 lm/W</li> <li>User-friendly installation and maintenance</li> </ul> | <br>M100L06   |
|  <b>LEDENVO® PLUS LED Street Light</b> | <ul style="list-style-type: none"> <li>S, 70W / 90W, 125-140 lm/W</li> <li>M, 120W / 150W, 125-140 lm/W</li> <li>L, 180W / 210W / 420W / 270W, 125-140 lm/W</li> </ul>                            | <ul style="list-style-type: none"> <li>Flexible power options</li> <li>IP66 protection and robust design</li> <li>High efficacy</li> <li>Professional optical design</li> <li>Long lifetime</li> <li>Environmental friendly</li> </ul>      | <br>M100L08   |
|  <b>LEDENVO® LED Street Light</b>    | <ul style="list-style-type: none"> <li>S, 30W, 110-120 lm/W</li> <li>M, 60W/90W, 110-120 lm/W</li> <li>L, 120W / 150W, 110-120 lm/W</li> </ul>                                                    | <ul style="list-style-type: none"> <li>Dual power source</li> <li>IP66 protection and robust design</li> <li>High efficacy</li> <li>Professional optical design</li> <li>Long lifetime</li> <li>Environmental friendly</li> </ul>           | <br>M200L08 |

## Flood Light

| Product                                                                                                                           | Description                                                                                                                                                            | Features & Benefits                                                                                                                                                                                                                                                                                       |                                                                                                  |
|-----------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|
|  <b>PURSOS® SHP V2 Square</b><br>(Coming soon) | <ul style="list-style-type: none"> <li>2 modules: 600W, 100-120 lm/W</li> <li>3 modules: 900W, 100-120 lm/W</li> <li>4 modules: 1200W, 100-120 lm/W</li> </ul>         | <ul style="list-style-type: none"> <li>Professional optical design with various lighting distribution options</li> <li>High power up to 1200W with comparable lumen output of traditional HID luminaire 2000W</li> <li>Light weight and compact</li> <li>Robust and reliable</li> </ul>                   | <br>M200L08 |
|  <b>PURSOS® SHP V2 Round</b><br>(Coming soon)  | <ul style="list-style-type: none"> <li>S: 450W, 120-130 lm/W</li> <li>M: 600W, 120-130 lm/W</li> <li>L: 800W, 120-130 lm/W</li> <li>XL: 1000W, 120-130 lm/W</li> </ul> | <ul style="list-style-type: none"> <li>Professional optical design with various lighting distribution options</li> <li>High power up to 1000W with comparable lumen output of traditional HID luminaire 2000W</li> <li>Light weight and compact</li> <li>Robust and reliable</li> </ul>                   | <br>M200L08 |
|  <b>Simplitz® LED Flood Light</b>              | <ul style="list-style-type: none"> <li>S, 70W / 100W, 121-135/W</li> <li>M, 150W / 200W, 118-133/W</li> <li>L, 240W / 280W, 116-128/W</li> </ul>                       | <ul style="list-style-type: none"> <li>True traditional 100W, 250W and 400W HID flood light replacement</li> <li>Tailored light distribution with asymmetric optic</li> <li>Tilt lockable yoke with aiming marks</li> <li>IP66 protection</li> <li>Light weight and compact with long lifetime</li> </ul> | <br>M100L12 |
|  <b>LEDCOMFO® Flood V3</b>                     | <ul style="list-style-type: none"> <li>S: 30W, 95 lm/W</li> <li>M: 45W, 105 lm/W</li> <li>L: 95W, 105 lm/W</li> <li>XL: 160 &amp; 190W, 105 lm/W</li> </ul>            | <ul style="list-style-type: none"> <li>Precise and efficient optics</li> <li>Full range for various applications</li> <li>Light weight and compact</li> <li>Robust and reliable</li> </ul>                                                                                                                | <br>M200L07 |

# Dynamic Lighting

## Architectural & Ambiance

### Façade Linear

|                                                                                     | Product                             | Type                             | Description                                                                                                                                                                           | Features & Benefits                                                                                                                                                  |                                                                                                  |
|-------------------------------------------------------------------------------------|-------------------------------------|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|
|    | <b>Allegro Linear AC</b>            | RGB, RGBW, Dynamic White, White  | <ul style="list-style-type: none"> <li>— 320 mm, 15W, 40-52 lm/W</li> <li>— 615 mm, 28W, 40-52 lm/W</li> <li>— 915 mm, 41W, 40-52 lm/W</li> <li>— 1215 mm, 55W, 40-52 lm/W</li> </ul> | <ul style="list-style-type: none"> <li>— High power &amp; efficacy</li> <li>— DMX with full RDM &amp; personality options</li> <li>— DynaMood® technology</li> </ul> | <br>M200L12   |
|    | <b>Nano Liner Allegro AC XB</b>     | RGB, Dynamic White, White        | <ul style="list-style-type: none"> <li>— 310 mm, 12.5W, 25 lm/W</li> <li>— 612 mm, 25W, 25 lm/W</li> <li>— 913 mm, 37.5W, 25 lm/W</li> <li>— 1216 mm, 50W, 25 lm/W</li> </ul>         | <ul style="list-style-type: none"> <li>— Highly efficacious &amp; energy efficient</li> <li>— DMX Control</li> <li>— Ultra slim exterior illumination</li> </ul>     | <br>M200L12   |
|    | <b>ARCHISHAPE® 2.0 Linear POWER</b> | On/Off, Dynamic White, RGB, RGBW | <ul style="list-style-type: none"> <li>— 300 mm, 19W / 20W, 35-45 lm/W</li> <li>— 500 mm, 27W / 34W, 35-45 lm/W</li> <li>— 1000 mm, 54W / 70W, 35-45 lm/W</li> </ul>                  | <ul style="list-style-type: none"> <li>— Slim size with high lumen output</li> <li>— Dedicated optic design</li> <li>— Easy installation and maintenance</li> </ul>  | <br>M200L12   |
|   | <b>ARCHISHAPE® 2.0 Linear MAXI</b>  | On/Off, Dynamic White, RGB, RGBW | <ul style="list-style-type: none"> <li>— 300 mm, 14W, 43-53 lm/W</li> <li>— 500 mm, 21W, 43-53 lm/W</li> <li>— 1000 mm, 42W, 43-53 lm/W</li> </ul>                                    | <ul style="list-style-type: none"> <li>— Slim size with high lumen output</li> <li>— Dedicated optic design</li> <li>— Easy installation and maintenance</li> </ul>  | <br>M200L12  |
|  | <b>ARCHISHAPE® 2.0 Linear MIDI</b>  | On/Off, Dynamic White, RGB, RGBW | <ul style="list-style-type: none"> <li>— 300 mm, 12W, 35-45 lm/W</li> <li>— 500 mm, 18W, 35-45 lm/W</li> <li>— 1000 mm, 36W, 35-45 lm/W</li> </ul>                                    | <ul style="list-style-type: none"> <li>— Slim size with high lumen output</li> <li>— Dedicated optic design</li> <li>— Easy installation and maintenance</li> </ul>  | <br>M200L12 |
|  | <b>ARCHISHAPE® 2.0 Linear MINI</b>  | On/Off                           | <ul style="list-style-type: none"> <li>— 300 mm, 3W / 6W, 73 lm/W</li> <li>— 500 mm, 4W / 9W, 73 lm/W</li> <li>— 1000 mm, 10W / 17W, 73 lm/W</li> </ul>                               | <ul style="list-style-type: none"> <li>— Slim size with high lumen output</li> <li>— Dedicated optic design</li> <li>— Easy installation and maintenance</li> </ul>  | <br>M200L12 |

### Façade Washer

|                                                                                     | Product                       | Type                            | Description                                                                                                                                                                                       | Features & Benefits                                                                                                                                                                                                                     |                                                                                                  |
|-------------------------------------------------------------------------------------|-------------------------------|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|
|  | <b>Allegro Washer AC</b>      | RGB, RGBW, Dynamic White, White | <ul style="list-style-type: none"> <li>— S, 50W, 30-50 lm/W</li> <li>— M, 100W, 30-50 lm/W</li> <li>— L, 150W, 30-50 lm/W</li> <li>— XL, 200W, 30-50 lm/W</li> </ul>                              | <ul style="list-style-type: none"> <li>— High power &amp; efficacy</li> <li>— 5° narrow beam</li> <li>— Filed installable spread lens</li> <li>— DMX with full RDM &amp; personality options</li> <li>— DynaMood® technology</li> </ul> | <br>M200L12 |
|  | <b>ARCHISHAPE® 2.5 Washer</b> | White / RGB / RGBW              | <ul style="list-style-type: none"> <li>— XS, 9W, 35-45 lm/W</li> <li>— S, 36W, 35-45 lm/W</li> <li>— M, 90W, 35-45 lm/W</li> <li>— L, 150W, 35-45 lm/W</li> <li>— XL, 200W, 35-45 lm/W</li> </ul> | <ul style="list-style-type: none"> <li>— Superior color mixing</li> <li>— DMX Control</li> <li>— Wide range of lumen output</li> <li>— Five beam options</li> </ul>                                                                     | <br>M200L12 |


## Media Solutions

### Dynamic Tube

|                                                                                     | Product                    | Type | Description                                                                                                                                                                                                                                                   | Features & Benefits                                                                                                                                                          |                                                                                                  |
|-------------------------------------------------------------------------------------|----------------------------|------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|
|  | <b>Media Tube® HO RGBW</b> | RGBW | Direct / Diffused <ul style="list-style-type: none"> <li>— 296 mm, 4.6W, 41 / 31 lm/W</li> <li>— 596 mm, 8.6W, 41 / 31 lm/W</li> <li>— 896 mm, 12.5W, 41 / 31 lm/W</li> <li>— 1196 mm, 16.6W, 41 / 31 lm/W</li> <li>— 1496 mm, 20.9W, 41 / 31 lm/W</li> </ul> | <ul style="list-style-type: none"> <li>— Various customization options</li> <li>— Flexible mounting capability</li> <li>— Daisy chain topology and simple cabling</li> </ul> | <br>M200L12 |

|                                                                                   |                                               |                                 |                                                                                                        |                                                                                                                                                                                                                                                                                     |                                                                                     |
|-----------------------------------------------------------------------------------|-----------------------------------------------|---------------------------------|--------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|  | <b>Media Tube®<br/>LITE RGBW</b>              | RGBW                            | <ul style="list-style-type: none"> <li>600 mm, 8.4W, 52 lm/W</li> <li>1000 mm, 14W, 52 lm/W</li> </ul> | <ul style="list-style-type: none"> <li>High performance</li> <li>Slim, rugged construction</li> <li>DMX Control</li> <li>Flexible options</li> </ul>                                                                                                                                |  |
|  | <b>Allegro Tube<br/>MONO</b><br>(Coming soon) | Cold<br>White,<br>Warm<br>White | <ul style="list-style-type: none"> <li>500 mm/ 995 mm/ 1490 mm</li> <li>59-62 lm/W</li> </ul>          | <ul style="list-style-type: none"> <li>IP66 rated slim profile LED tube</li> <li>Quick-lock connector for faster installation and reliability</li> <li>Longer daisy chain up to 20m per power supply</li> <li>Available in different CCT, as well as single color option</li> </ul> |  |

## Dynamic Dot

| Product                                                                            | Type                           | Description                                                                                                                                           | Features & Benefits                                                                                                                                                                                                                                           |                                                                                                 |
|------------------------------------------------------------------------------------|--------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|
|   | <b>Allegro Dot</b>             | RGB /<br>RGBW /<br>White /<br>Dynamic<br>White<br><br>Direct / Diffused<br>— S, 1W, up to 48 lm/W<br>— M, 2W, up to 51 lm/W<br>— L, 3W, up to 49 lm/W | <ul style="list-style-type: none"><li>— The number of dots per string and pixel pitch can be fully customized</li><li>— ConnectOne (Failure detection per string with RDM communication)</li><li>— WhiteOne (Improve white element display quality)</li></ul> | <br>M200L12  |
|   | <b>ARCHISHAPE®<br/>2.0 Dot</b> | RGB,<br>RGBW,<br>White,<br>Dynamic<br>White<br><br>Direct / Diffused<br>— S, 1W, up to 29 lm/W<br>— M, 2W, up to 41 lm/W<br>— L, 3W, up to 39 lm/W    | <ul style="list-style-type: none"><li>— The number of dots per string and pixel pitch can be fully customized</li><li>— DMX control with auto-addressing</li><li>— Achieve longer daisy chain by power injection</li></ul>                                    | <br>M200L12  |
|  | <b>String / Mesh</b>           | RGB<br><br>String<br>— 2300 mm, 98W<br><br>Mesh<br>— 2000 mm, 98W                                                                                     | <ul style="list-style-type: none"><li>— Flexible mounting capability</li><li>— Low-to-medium resolution</li><li>— Outdoor-rated</li><li>— Smart Chip technology</li><li>— Back-to-back mounting capability (Mesh only)</li></ul>                              | <br>M100L12 |

## Dynamic Board

| Product                                                                             | Type                                       | Description                                                                                                                                                                                                                                | Features & Benefits                                                                                                                                                                                                             |                                                                                                   |
|-------------------------------------------------------------------------------------|--------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------|
|  | <b>16 / 64 PXL Board</b><br><b>RGB 2.0</b> | RGB<br><br>16PXL Board <ul style="list-style-type: none"><li>— 230 mm x 230 mm x 11.5 mm</li><li>— 8W, 18 lm/W</li></ul><br>64PXL Board <ul style="list-style-type: none"><li>— 240 mm x 240 mm x 11.5 mm</li><li>— 24W, 24 lm/W</li></ul> | <ul style="list-style-type: none"><li>— 30 fps on DMX control, 60 fps on e:pix</li><li>— Automatic switching between DMX and e:pix protocol</li><li>— Fiberglass reinforced board</li><li>— Versatile mounting option</li></ul> | <br>M100L08  |
|  | <b>16PXL Strip</b><br><b>RGB 2.0</b>       | RGB<br><br>— 499 mm x 15 mm x 10 mm<br>— 8W, 18 lm/W                                                                                                                                                                                       | <ul style="list-style-type: none"><li>— 30 fps on DMX control, 60 fps on e:pix</li><li>— Automatic switching between DMX and e:pix protocol</li><li>— Fiberglass reinforced board</li><li>— Versatile mounting option</li></ul> | <br>M100L 08 |

## Stage Lighting

| Product                                                                             | Type                                   | Description                                                                                                                                                                                                       | Features & Benefits                                                                                                                                                                                                                                                                                                                                     |                                                                                                  |
|-------------------------------------------------------------------------------------|----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|
|  | <b>Xtylos</b><br>(from Clay Paky)      | RGB <ul style="list-style-type: none"><li>— 391 mm (W) x 603 mm (H) x 294 mm (D)</li><li>— 400 VA</li><li>— IP54 protection with "Igloo" enclosure</li></ul>                                                      | <ul style="list-style-type: none"><li>— RGB additive color mixing with exclusive Turbo-colors by Tailor-made laser technology</li><li>— Natural beam aperture: 2° (up to 0.5° using beam diameter reducers)</li><li>— "Blazer" effect with 7 rotating gobos / 12 fixed gobos / 4 prisms and 1 frost filter</li><li>— Input: DMX 512 – Art-Net</li></ul> | <br>M024L08 |
|  | <b>Odeon Flood</b><br>(from Clay Paky) | RGBW /<br>Dynamic White /<br>White <ul style="list-style-type: none"><li>— MAXI: 320W, 27 lm/W (RGBW)</li><li>— MEDIUM: 250W, 23 lm/W (RGBW)</li><li>— MINI: 175W, 20 lm/W (RGBW)</li><li>— IP65 - IK09</li></ul> | <ul style="list-style-type: none"><li>— High-power multi-chip LED technology to ensure excellent color mixing &amp; DMX/RDM dimming</li><li>— Perfect color uniformity by exclusive "Hexeel" optical system</li><li>— Available with various optical units (15°, 25° and 35°)</li></ul>                                                                 | <br>M024L08 |
|  | <b>Glow Up</b><br>(from Clay Paky)     | RGBW /<br>Dynamic White /<br>White <ul style="list-style-type: none"><li>— 226mm (ø) x 327mm (H)</li><li>— 50W, 24 lm/W</li><li>— IP65</li></ul>                                                                  | <ul style="list-style-type: none"><li>— A portable, battery-powered luminaire that easy for logistic</li><li>— The battery can be recharged 2000 times</li><li>— Installation, set-up and control is entirely wireless and without cables.</li><li>— DMX recorder for memorizing cues programmed by the user</li></ul>                                  | <br>M024L08 |

# Control & Software

## DMX & e:pix

| Product                                                                             | Description                                                                                                                                                                                                                                                                              | Features & Benefits                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                                                                                                                            |
|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|    | <b>Lighting Control Engine 2 / 2 fx</b> <ul style="list-style-type: none"> <li>115W</li> <li>190W (2 fx)</li> <li>491 mm (W) x 176 mm (H) x 432 mm (D)</li> </ul>                                                                                                                        | <ul style="list-style-type: none"> <li>e:cue Lighting Application Suite pre-installed</li> <li>High quality components for reliable uninterrupted operation</li> <li>Integrated DMX inputs and outputs, dry contact input, relay outputs</li> <li>LC display and cursor keys for status messages and control</li> <li>Support for a variety of Ethernet-based protocols</li> <li>Easily mountable in 19 inch rack</li> </ul> <p>Addition features on 2 fx</p> <ul style="list-style-type: none"> <li>Emotion FX in full production edition</li> <li>High performance graphics for video sequencing</li> </ul>                                                      |  M001L08<br> M001L08 |
|    | <b>Butler PRO</b> <ul style="list-style-type: none"> <li>20W max.</li> <li>482 mm (W) x 44 mm (H) x 142 mm (D)</li> </ul>                                                                                                                                                                | <ul style="list-style-type: none"> <li>Easily mountable</li> <li>Status message display</li> <li>Backup image</li> <li>Versatile test mode</li> <li>Supports RDM protocol for bidirectional communication (DMX512/RDM version only)</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                     |  M001L12                                                                                                |
|    | <b>Butler S2</b> <ul style="list-style-type: none"> <li>2.7W (incl. DMX termination)</li> <li>71.5 mm (W) x 24 mm (H) x 85 mm (D)</li> </ul>                                                                                                                                             | <ul style="list-style-type: none"> <li>Control up to 1,024 DMX Channels/2 DMX512 Universes</li> <li>Support RDM protocol for bidirectional communication</li> <li>Integrated web server for setup</li> <li>Store and replay pre-programmed cues</li> <li>Scalable up to 64 devices (128 DMX512 Universes) in standalone mode 16 devices, also mix with XT2 up to 32 Universes</li> <li>Reliable uninterrupted operation</li> </ul>                                                                                                                                                                                                                                 |  M001L12                                                                                                |
|  | <b>Butler XT2</b> <ul style="list-style-type: none"> <li>12-24V DC, &gt; = 1,3 A with e:bus 24V DC</li> <li>177 mm (W) x 60 mm (H) x 75 mm (D)</li> </ul>                                                                                                                                | <ul style="list-style-type: none"> <li>Up to eight independently controlled zones in standalone mode</li> <li>Control up to 1,024 DMX512/RDM channels</li> <li>RDM protocol for bidirectional communication</li> <li>Internal real-time and astronomical clock with daylight savings options</li> <li>Easily upload lighting show files via Ethernet</li> <li>Reliable uninterrupted operation</li> <li>Scalable up to 65,536 channels in online mode, 16,384 in standalone mode with more XT2 devices or in combination with Butler S2</li> <li>Integrated webserver, remote control of lighting shows via web browser or iOS-systems, Android Systems</li> </ul> |  M001L12                                                                                              |
|  | <b>Video Micro Converter</b> <ul style="list-style-type: none"> <li>12V DC, 5W (ext. PSU)</li> <li>155 mm (W) x 120 mm (H) x 45 mm (D)</li> </ul>                                                                                                                                        | <ul style="list-style-type: none"> <li>Simple video-to-LED solution</li> <li>Support DVI input resolutions up to 1,080p (1,920 x 1,080 pixels)</li> <li>Highly versatile pixel mapping capabilities</li> <li>Configurable DMX512 monochrome or color channel mapping</li> <li>Grab and convert up to 4,096 DVI pixels per VMC (DMX512 mode) and 4,096 pixels (e:pix mode)</li> <li>Internal active DVI signal booster</li> <li>Configurable startup delay</li> <li>Stored default image in case of video input loss</li> <li>Arrange lighting fixture and set up VMCs using the e:cue software suite</li> </ul>                                                    |  M001L12                                                                                              |
|  | <b>RDM Isolator</b> <ul style="list-style-type: none"> <li>9-48V DC, 1W (ext.)</li> <li>71 mm (W) x 24 mm (H) x 80 mm (D)</li> </ul>                                                                                                                                                     | <ul style="list-style-type: none"> <li>1 kV isolation</li> <li>USITT DMX512A and e:pix compatibility</li> <li>1Mbaud data speed (e:pix)</li> <li>RJ45 power back selectable</li> <li>Separate, fully isolated power supply port</li> <li>Flexible data ports (RJ45 or screw terminals)</li> <li>Full ANSI E1.20-2010 RDM support</li> <li>Status LEDs</li> </ul>                                                                                                                                                                                                                                                                                                   |  M001L12                                                                                              |
|  | <b>SYMPL Modular Controller Range</b> <ul style="list-style-type: none"> <li>SYMPL Core S</li> <li>SYMPL dmx Node</li> <li>SYMPL e:pix Node</li> <li>SYMPL dali Node</li> <li>SYMPL input Node</li> <li>SYMPL serial Node</li> <li>SYMPL relay Node</li> <li>SYMPL e:bus Node</li> </ul> | <ul style="list-style-type: none"> <li>Scalable control solution on a unified Ethernet-based system bus</li> <li>Control DALI and DMX fixtures with one system</li> <li>Extend systems with additional devices at any time</li> <li>Setup lighting control networks with a fingertip</li> <li>Adapt lighting control systems flexibly if requirements change in any project phase</li> </ul>                                                                                                                                                                                                                                                                       |  M001L12                                                                                              |

## Software

| Product                                                                                                                 | Description                                                                                                                                                                                                                          | Features & Benefits                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                                |
|-------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|
|  <b>SYMPHOLIGHT</b>                    | <ul style="list-style-type: none"> <li>e:cue SYMPHOLIGHT is a simple yet powerful lighting control software with an intuitive graphic user interface.</li> </ul>                                                                     | <ul style="list-style-type: none"> <li>Timeline-based programming</li> <li>Modern layer design for media, effects and blending modes</li> <li>Patching, programming and execution in one single application</li> <li>Easy content creation and dynamic lighting effects editing</li> <li>Rich built-in Effects Library with customizable color and intensity effects</li> <li>Device Library with Traxon, e:cue and generic devices</li> <li>Real-time programming, editing and preview</li> <li>Enhanced flexibility and stability via separated design and execution stages</li> <li>Simulation capability for both design and execution stages</li> <li>Powerful and flexible Trigger engine with Conditions and Actions for automation and control</li> <li>Extendable with C# scripting macros</li> <li>HTML5-based Graphic User Interface (GUI) Editor for wired or wireless show control via any web browser</li> </ul> | <br>M001L12 |
|  <b>Lighting Application Suite 7.0</b> | <ul style="list-style-type: none"> <li>The Lighting Application Suite (LAS) 7.0 combines DMX, e:pix and DALI lighting, multimedia, and show control programming with unrivalled connectivity and matrix control features.</li> </ul> | <ul style="list-style-type: none"> <li>DALI Manager integrating DALI ballasts and sensors for use with the ETH2DALI Interface</li> <li>Conditional Triggering and extended trigger rules for more advanced automation</li> <li>Background pictures from Patchelor now imported and shown in Preview Window</li> <li>Sequencer can be synchronized to MTC and SMPTE</li> <li>Bitmap Wizard now supports animation of Programmer View</li> <li>Several e:script commands added</li> <li>Patchfile import with additive or replacing patch mode of fixtures</li> </ul>                                                                                                                                                                                                                                                                                                                                                            | <br>M001L12 |

## DALI & Dimming

| Product                                                                                                                      | Description                                                                                                                                                                                                                                                                         | Features & Benefits                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                                                                                  |
|------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|
|  <b>DMX2CC 6 &amp; 12 channels</b>        | <b>6 Channels</b> <ul style="list-style-type: none"> <li>24-48V DC, max. 4.5 A</li> <li>142 mm (W) x 75.4 mm (H) x 58.5 mm (D)</li> </ul> <b>12 Channels</b> <ul style="list-style-type: none"> <li>24-48V DC, max. 9 A</li> <li>272 mm (W) x 75.4 mm (H) x 58.5 mm (D)</li> </ul>  | <ul style="list-style-type: none"> <li>Smooth, flicker-free dimming of constant current fixtures</li> <li>Pre-selectable LED current between 50 mA to 700 mA</li> <li>DMX512 in/out with auto/manual addressing options</li> <li>Self-diagnostic test function, overheating protection and overcurrent protection</li> <li>Status message display and keys for configuration and setup</li> <li>High efficiency (up to 95%)</li> </ul>                               | <br>M001L12 |
|  <b>DMX2PWM 3 &amp; 9 channels Dimmer</b> | <b>3 Channels</b> <ul style="list-style-type: none"> <li>12-48V DC (screw term.)</li> <li>142 mm (W) x 75.4 mm (H) x 58.5 mm (D)</li> </ul> <b>9 Channels</b> <ul style="list-style-type: none"> <li>12-48V DC (screw term.)</li> <li>107 mm (W) x 76 mm (H) x 59 mm (D)</li> </ul> | <ul style="list-style-type: none"> <li>Control of constant voltage LED fixtures</li> <li>3/9 individually-controllable output channels via DMX512</li> <li>Reverse supply protection and overcurrent protection (self-resetting)</li> <li>Smooth dimming via PWM with 488 Hz frequency</li> <li>Manual address setting or auto-addressing selectable</li> <li>Input voltage range: 12-48 VDC</li> <li>14bit PWM resolution calculated from 8bit DMX value</li> </ul> | <br>M001L12 |

### For enquiry, please contact:

**Hong Kong**  
(Asia Pacific Headquarters)  
Traxon e:cue  
info@traxontechnologies.com /  
traxon.ecue.newsletter@osram.com

1st Oct 2019 Edition

**Korea**  
Phone: +82 2 3490 3600  
Fax: +82 2 554 5611

**Singapore**  
Phone: +65 65 52 0110  
Fax: +65 65 52 7117

**Malaysia**  
Phone: +603 7959 0000  
Fax: +603 7959 0011

**Indonesia**  
Phone: +62 21 6570 4100  
Fax: +62 21 6570 4101

**Thailand**  
Phone: +662 763 5755  
Fax: +662 763 5756

**Japan**  
Phone: +81 45 548 6167  
Fax: +81 45 548 6816

### Connect with us on Social Media



### Download our Mobile App

